## Open Frame

## Open Frame High Brightness Display

5.7"


Alt

## **Specifications**

E	₹0	N.	30	2
C	OM	IPL	۱AI	41.

Model Name	R05T100-OFD1HB		
Panel Size	5.7" (4:3)		
Active Dipsplay Area(mm)	115.2 (H) x 86.4(V)		
Resolution	640x480		
Contrast Ratio	300:1 (Typical)		
Display Color	262K (6 bit/color)		
Brightness(cd/m2)	900 (Typical)		
Viewing Angle(CR>=10)	-70~70(H); -40~60(V)		
Standard Input Signal	1 x VGA, 1 x HDMI		
Accessories	Power Adapter		
	VGA cable		
	HDMI Cable		
	13 Keys IR remote control pad (Optional)		
Power Input	12V DC in,		
	with external AC to DC Adapter (100 to 240VAC)		
Power Consumption	15 W typical, Normal operation		
Operating tempurature	0~50°C		
Storage Tempurature	-10~60 °C		
Storage Tempurature Touch Screen (Optional)	-10~60 °C P-cap. (Customized)		
	P-cap. (Customized)		
Touch Screen (Optional)	P-cap. (Customized) Resistive		
Touch Screen (Optional)  Remote Control (Optional)*	P-cap. (Customized) Resistive RS232 port		







- 1. Touch (Optional)
- 2. VGA
- 3. HDMI
- 4. 12V DC-in

\* When adding the function, the outside dimension may change.

## **Mechanical Drawing**





UNIT:mm

\* Note: this is a simplified drawing and some components are not marked in detail.

Please contact our sales representative if you need further product information.

74,5±0,5

74,5±0,5